

Compass[®] 360

TOUCHPAD

7-INCH TOUCH SCREEN

Responsive single pane capacitive touch screen.

ONE-PIECE GLASS FACE

ACCESSIBILITY BUTTON

HIDDEN SPEAKER

OPTIONAL CARD READER WITH LIGHTED LOGO



White

Black

Silver

Gold



AVAILABLE IN
ANGLE OR FLUSH
MOUNTED DESIGNS.

SELECT FROM 4 COLOR
COMBINATIONS.

OTIS

Learn more at [otis.com](https://www.otis.com)

© 2020 OTIS ELEVATOR COMPANY.

Compass[®] 360

TOUCHPAD – TECHNICAL SPECIFICATIONS

TOUCHPAD		
MOUNTING OPTIONS	ANGLED	FLUSH
Dimensions H x W x D	296.5 x 128 x 61.5mm (11.7 x 5.0 x 2.4in)	371 x 168 x 97.5mm (14.6 x 6.6 x 3.8in)
Energy Consumption Optional RFID reader adds 0.6W to max	200mA @ 48VDC (9.6W)	
Screen	7-inch Capacitive Touch Screen with 600 x 1024dpi resolution	
Standby	Yes, after a selectable period of non-operation	
Temperature Range	Temperature: 0-40 degrees C (32-104 degrees F)	

CARD READER INFORMATION

Optional multiple integrated reader technologies available.
Talk to your Otis Elevator Representative for more information on available reader types and capabilities.

Types of Card Readers	RFID: Elatec TWN4 MultiTech 2 PI ¹
	RFID/Mobile capability, DirectKey (Blue Diamond App); HID RFID and HID Mobile App.
Supported Frequencies	125kHz/134kHz, 13.56MHz, 2.4-2.48GHz
Protocols	ISO14443A, ISO14443B, ISO18092, ISO15693

1. Default selection 2. Optional selection

COMPLIANCE

Elevator Safety Code Compliance	North America: ASME A17.1-2016/ CSA B44-16
	Other Regions: EN81-20 , EN-81-50
Accessibility Code Compliance	North America: A117.1–2017
	Other Regions: EN81-70:2018
EU Reach Compliance	Article 33

CALIFORNIA COMPLIANCE



OTIS

Learn more at [otis.com](https://www.otis.com)

© 2020 OTIS ELEVATOR COMPANY.